## What is claimed is:

1. An optical data recording medium comprising a transparent substrate, a thin film layer formed on the transparent substrate and a protective film which is mainly comprised of a resin and formed on the thin film layer for protecting the thin film layer, wherein the thin film layer is a single layered or multilayered film including at least any one of a dielectric film, a recording film and a reflective film, and at least either one of a linear expansion coefficient and a Young's modulus of the protective film is greater than that of the transparent substrate, the linear expansion coefficient of the protective film being greater than  $7.0 \times 10^{-5}$  ( $1/^{\circ}$ C) and smaller than  $5.0 \times 10^{-4}$  ( $1/^{\circ}$ C).

15

20

25

10

5

2. An optical data recording medium comprising a transparent substrate, a thin film layer formed on the transparent substrate and a protective film which is mainly comprised of a resin and formed on the thin film layer for protecting the thin film layer, wherein the thin film layer is a single layered or multilayered film including at least any one of a dielectric film, a recording film and a reflective film, and at least either one of a linear expansion coefficient and a Young's modulus of the protective film is greater than that of the transparent substrate, the Young's modulus of the protective

10

25

film being greater than  $2.0 \times 10^9$  (Pa) and smaller than  $1.0 \times 10^{10}$  (Pa).

- An optical data recording medium according to any
   one of claims 1 and 2, wherein a thickness of the protective film is 5 μm or more to 20 μm or less.
  - 4. An optical data recording medium according to claim 1, wherein the linear expansion coefficient of the protective film is 1.5 to 3 times as great as that of the transparent substrate, the linear expansion coefficient being greater than  $1.0 \times 10^{-4}$  (1/°C) and smaller than  $2.0 \times 10^{-4}$  (1/°C).
- 5. An optical data recording medium according to any
  one of claims 1 and 2, wherein the transparent substrate is
  made of a polycarbonate or a polyolefin and a thickness thereof
  is about 0.5 mm.
- 6. An optical data recording medium according to any one of claims 1 and 2, wherein the protective film is made of an ultraviolet light curing resin.
  - 7. A method of selecting a protective film in an optical data recording medium, the optical data recording medium comprising a transparent substrate, a thin film layer formed on

5

10

15

20

25

the transparent substrate and the protective film which is mainly comprised of a resin and formed on the thin film layer for protecting the thin film layer, wherein, on condition that the thin film layer is a single layered or multilayered film including at least any one of a dielectric film, a recording film and a reflective film and the transparent substrate is made of a polycarbonate or a polyolefin with a thickness of 0.5 mm, the protective film is selected such that at least either one of a linear expansion coefficient and a Young's modulus of the protective film is greater than that of the transparent substrate and the linear expansion coefficient of the protective film is greater than  $7.0 \times 10^{-5}$  (1/°C) and smaller than  $5.0 \times 10^{-4}$  (1/°C).

8. A method of selecting a protective film in an optical data recording medium, the optical data recording medium comprising a transparent substrate, a thin film layer formed on the transparent substrate and the protective film which is mainly comprised of a resin and formed on the thin film layer for protecting the thin film layer, wherein, on condition that the thin film layer is a single layered or multilayered film including at least any one of a dielectric film, a recording film and a reflective film and the transparent substrate is made of a polycarbonate or a polyolefin with a thickness of 0.5 mm, the protective film is selected such that at least either one of a linear expansion coefficient and a Young's modulus of the

protective film is greater than that of the transparent substrate and the Young's modulus of the protective film is greater than  $2.0\times10^9$ (Pa) and smaller than  $1.0\times10^{10}$ (Pa).

5 9. An optical data recording medium provided with a protective film for protecting a thin film layer selected by the method of claim 7 or 8.